

CM-02 AC/DC Clamp Meter Automotive Clamp



Features

- ◆ DC/AC 10mA Resolution
 - ◆ 23mm Jaw Diameter
 - ◆ Auto Range V , A, Ω , F and Temperature
 - ◆ AC/DC 0.01~200A
 - ◆ One Touch Zero for DCA adjustment
 - ◆ 3 3/4 Digits (4,032 Counts)
 - ◆ Capacitance & Diode Measurement
 - ◆ Temperature: °C, °F seletable
 - ◆ Max / Min, Date Hold
- **AC/DC Current:** 40/200A
 - **AC/DC Voltage:** 400mV/4/40/400/600 V
 - **Resistance:** 400/4K/40K/400K/4M/40M Ω
 - **Frequency:** 1~100KHz
 - **Continuity:** 40~400 Ω
 - **Temperature:** -40~1000°C , -40~1800°F

CM-05 AC/DC Current Probe



Features

- ◆ Accurate DC/AC current probe
 - ◆ 10mADC, 1mAAC high resolution
 - ◆ 23mm Jaw Diameter
 - ◆ One Touch Zero for DCA adjustment
 - ◆ Easy single rotary switch for any function selection
- **AC/DC Current:** 4A/40A/150A/200A
 - **Sensitivity:** 0.1mV/1 mA, 0.1mV/10 mA, 0.1 mV/100 mA

CM-07 TRMS AC/DC Clamp Meter



Features

- ◆ High Resolution DC 10mA, AC 1mA
- ◆ True RMS reading
- ◆ Non-contact Current, Frequency Measurement
- ◆ 23mm Large Jaw Diameter
- ◆ One Touch Zero for DCA adjustment
- ◆ Large 3 3/4 Digits LCD(4032 counts)
- ◆ Fast Analog Bargraph Display
- ◆ Max/Min, Data Hold
- **AC/DC Current:** 40A/150A/200A/400A (DC), 4A/40A/100A/200A/400A (AC)
- **Frequency:** 1~100K Hz

Prova 11 AC/DC mA TRMS Clamp Meter



Features

- ◆ Super High Resolution-DC/1 mA, AC/0.1mA
- ◆ True RMS
- ◆ One Touch Zero for DCA adjustment
- ◆ 23mm jaw diameter
- ◆ Lager 3 3/4 Digits LCD(4032 counts)
- ◆ Fast bargraph display
- ◆ Max/Min, Data Hold
- **AC/DC Current:** 0~4A/30A/40A(DC), 400mA/4,000mA/30A(AC)
- **AC/DC Voltage:** 400 V