

CENTER 321 Sound Level Meter



- RS-232 Interface
- Bar Graph Indication
- MAX/MIN Function
- Auto Ranging(30~130dB)
- Resolution 0.1dB
- Clock Display
- Level Range Display
- AC/DC Signal Output

Microphone:

Electrode condenser microphone

Accuracy:

± 1.5 dB (ref 94dB @1KHz)

Level Range:

Lo = 30 ~ 80 dB

Med = 50 ~ 100 dB

Hi = 80 ~ 130 dB

Auto=30~130 dB

Frequency Weighting:

A , C

Time Weighting:

Fast , Slow

Auxiliary Outputs:

AC output

Output voltage: 1Vrms (at full scale)

Output impedance: Approx:600 Ω

AC output

Output voltage: 10mV / dB

Output impedance: Approx:50 Ω

Dynamic Range:

50 dB

Frequency Range:

31.5Hz to 8KHz

Battery Type:

9V Battery

Battery Life:

50 hours (with alkaline battery)

Operation Temp.:

0 °C~ 40 °C(<80% R.H.) 9V Battery, Carrying Case, Calibration Screwdriver, Windscreen

Accessories:

Battery, Operation Manual, Carrying Case, Calibration Screwdriver, Windscreen, 3.5Φ plug