

APECH

AC-368



Features

- 3 1/2 digit LCD display, maximum display: 1999
- 2A ~ 600A AC current clamp measurement.
- AC /DC μ A , mA measurement by test lead.
- Overvoltage level reaches safety CATIII 600V.
- Backlight function.
- Flashlight function
- Maximum hold MAX
- Battery powered 1.5V x 3

Specifications

Function	Range	Resolution	Accuracy
DC voltage (DCV)	200mV	0.1mV	$\pm 0.5\%$ rd + 5dgt
	2V	1mV	
	20V	10mV	
	200V	100mV	$\pm 0.8\%$ rd + 15dgt
	600V	1V	
AC voltage (ACV)	200mV	0.1mV	$\pm 1.0\%$ rd + 5dgt
	2V	1mV	
	20V	10mV	
	200V	100mV	$\pm 1.5\%$ rd + 15dgt
	600V	1V	
DC current (measurement by Test Lead) (DCA)	200 μ A	0.1 μ A	$\pm 2.0\%$ rd + 5dgt
	2000 μ A	1 μ A	$\pm 2.0\%$ rd + 5dgt
	20mA	10 μ A	$\pm 2.0\%$ rd + 5dgt
	200mA	100 μ A	$\pm 2.0\%$ rd + 10dgt
AC current (measurement by Test lead) (ACA)	200 μ A	0.1 μ A	$\pm 2.0\%$ rd + 8dgt
	2000 μ A	1 μ A	$\pm 2.0\%$ rd + 8dgt
	20mA	10 μ A	$\pm 2.0\%$ rd + 8dgt
	200mA	100 μ A	$\pm 2.5\%$ rd + 10dgt
AC current (measurement by Clamp) (ACA)	2A	1mA	$\pm 2.5\%$ rd + 10dgt
	20A	10mA	$\pm 2.5\%$ rd + 5dgt
	200A	100mA	$\pm 2.5\%$ rd + 5dgt
	1000A	1A	$\pm 2.5\%$ rd + 10dgt
	200 Ω	0.1 Ω	$\pm 0.8\%$ rd + 10dgt
Resistance (Ω)	2K Ω	1 Ω	$\pm 0.8\%$ rd + 8dgt
	20K Ω	10 Ω	
	200K Ω	100 Ω	
	2M Ω	1K Ω	
	20M Ω	10K Ω	$\pm 1.0\%$ rd + 25dgt
Diode test	✓		
Continuity test	✓		
Auto Power Off	✓		
Data Hold	✓		
backlight	✓		
Analog display	✓		
Low Battery Indicator	✓		
Symbol display	✓		
NCV measurement	✓		
Flashlight	✓		
Battery	4.5V = (1.5V x 3)		