

# APECH

## AM-288



## AM-288C



## AM-288K



### Features

- AM-288, AM-288C, AM-288K is model multimeter is a original versatile meter, with 22 basic quality limit and 6 additive quality limit. It have circuit protect equipment which including diode. The covering is a glass cover whis is clear& compression resistance. It is wildly used in many field, is a most popular multimeter in export and import
- Heavy ABS housing plus compact protective holster alongside
- 21-25 test ranges, 11 working functions
- High Input Impedance:DC 20KΩ/V,AC 9KΩ/V
- Strong Magnet Pivot-Jwell Movement built-in
- Compact soft Protective Holster alongside
- Perfect Overload Protection including Two fast-acting Fuses 0.5A & 10A
- Adjustable Rear tilt stand device with Hook-up place

### Specifications

AM-288		
Function	Range	Accuracy
AC Voltage	10/50/250/1000V	±5.0% F.S.
DC Voltage	0.1/2.5/10/50/250/1000V	±4.0% F.S.
DC current	0.5/2.5/25/250mA,10A	±4.0% F.S.
Resistance	X1,X10,X100,X1K(C1),X10K(0.2~20MΩ)	±4.0% F.S.
Capacitance (Test With CT-1)	C1:100pF~0.025uF/25uF , C2: upto 2000uF	±3.0% F.S
NULL Center	±DCV 5V/25V Test	±5.0% F.S
Decibels Test	-20~+62dB with an external Polyester capacitor 0.047uF/400V	
Continuity	Test With Buzzer	
Battery Test	1.5V,9V	
Leakage Current & Diode Test	YES	
Transistor & LED Test	YES	
Dimension & Weight	158*105*40mm & 350g approx	
Power Supply	6F22 9V battery 1pc, AA size 1.5V battery 2pcs	
Safety Over voltage Category	CAT III 500V, CAT II 1000V	
AM-288C		
Function	Range	Accuracy
AC Voltage	10/50/250/1000V	± 5% of FS
DC Voltage	0.25/2.5/10/50/250/1000V	± 4% of FS
DC Current	0.1/2.5/25/250mA,10A	±4% of FS
Resistance	X1,X10,X100,X1K(C1),X10K(0.2~20MΩ)	± 4% of FS
Capacitance Test With Tool Kit(CT-2)	C1:100pF~0.025uF/2.5uF/25uF	±3.0% of F.S.
Decibels Test	-20~+62dB with an external Polyester capacitor 0.047uF/400V	
Continuity Test With Buzzer	YES	
Battery Test:	1.5V,9V	
Leakage Current & Diode Test	YES	
Transistor & LED Test via hFE socket	YES	
Dimensions & Weight:	160*105*40mm & 340g approx.	
Power Supply	6F22 9V 1pc, AA size 1.5V 2pcs	
Safety Over -voltage Category	CAT III 500V, CAT II 1000V	
AM-288K		
Function	Range	Accuracy
AC Voltage	10/50/250/1000V	± 5% of FS
DC Voltage	0.25/2.5/10/50/250/1000V	± 4% of FS
DC Current	0.1/2.5/25/250mA,10A	±4% of FS
Resistance	X1,X10,X100,X1K(C1),X10K X 100K (0.2~200MΩ)	± 4% of S.Length
Capacitance Test With Tool Kit(CT-1)	C1:100pF~0.025uF/2.5uF/25uF, C2:upto 2000uF	±3.0% of F.S.
Decibels Test	-20~+62dB with an external Polyester capacitor 0.047uF/400V	
Continuity Test With Buzzer	YES	
Battery Test:	1.5V,9V	
Leakage Current & Diode Test	YES	
Transistor & LED Test via hFE	YES	
Dimensions & Weight:	160*105*40mm & 340g approx.	
Power Supply	6F22 9V 1pc, AA size 1.5V 2pcs	
Safety Over -voltage Category	CAT III 500V, CAT II 1000V	

