

# Noise dosimeter SD card data recorder

Carrying case  
( included )



Microphone with clip  
( included )

Carrying case  
( included )



Microphone with clip  
( included )

## compact size + data logger NOISE DOSIMETER

### Model : DS-9200

- \* Standards IEC61252, ANSI S1.25 for noise dose and sound exposure meters, IEC 61672 Class 2 / ANSI S1.4 Type S for sound level meters.
- \* A or C frequency weighting.
- \* Ranges : 30 to 130 dB auto range.
- \* Display : LCD, 0.01-9999 %.
- \* Criterion Level : 80, 84, 85 or 90dB.
- \* Exchange rate : 3, 4, 5 or 6 dB.
- \* Threshold level : 70 to 90 ( 1 dB steps ).
- \* Response rate : Fast or Slow.
- \* Measurement duration : 0/1/5/10/15/30 minutes 1/2/4/8/10/12/24 hours.
- \* Microphone : 1/2 inch electret condenser.
- \* Data logger no. : 16000 no. max..
- \* Size : 107 x 58 x 25 mm.
- \* Microphone with the clip and the carrying case are included.
- \* Optional Excel data transmission software, SW-E2005.

## SD card data recorder

### NOISE DOSIMETER

### Model : DS-2013SD

- \* Standards IEC61252, ANSI S1.25 for noise dose and sound exposure meters, IEC 61672 Class 2 / ANSI S1.4 Type S for sound level meters.
- \* A or C frequency weighting.
- \* Ranges : 30 to 130 dB auto range.
- \* Display : LCD, 0.01-9999%.
- \* Criterion Level : 80, 84, 85 or 90dB.
- \* Exchange rate : 3, 4, 5 or 6 dB.
- \* Threshold level : 70 to 90 ( 1 dB steps ).
- \* Response rate : Fast or Slow.
- \* Measurement duration : 0/1/5/10/15/30 minutes 1/2/4/8/10/12/24 hours.
- \* Microphone : 1/2 inch electret condenser.
- \* RS232/USB computer Interface.
- \* Real time data logger, saving data can export to SD card with Excel file, then user can download it to the Excel, extra software is no need.
- \* SD memory card capacity : 1 GB to 16 GB.
- \* Size: 132 x 80 x 32 mm.
- \* Microphone with the clip and the carrying case are included.