

SGT Docking Station

SENKO



Description

Docking station maximizes the performance of SGT device. It calibrates and does bump test up to four SGT device simultaneously, helping to reduce time. Through Bump test, Docking station tests the gas sensor response and alarm of the devices. In addition, it automatically upgrades the firmware of the devices when the devices are connected to Docking station. Event logs are saved into the USB memory and provide analyses for users. The configuration can be set by connecting Docking station with IR link.

Key Feature

- Calibration, Bump Test
- Displays status on Power LED and Unit LED
- Saves the status and results of Docking station and SGT
- Upgrades Docking and SGT Firmware
- Saves the log data of Docking station and SGT
- Supports user options using a PC program (IR Link/USB)

Specification

Model	SGT Docking Station
Size	47 × 41 × 22cm (18.50 × 16.14 × 8.66 in.)
Weight (Without gas cylinder)	8.2kg
Operating Temperature	41 to +104°F (5 to +40°C)
Warrenty	Full 2 years
Battery Type	Rechargeable Lithium Ion
Battery Life	1000 Bump Tests
LEDs	5 red/green/orange LEDs(1 for each unit, 1 for power)
Memory	USB 8GB Standard
Log Capacity	Approximately Up to 10 million tests (8GB,removable USB memory)
Tests Performed	Bump Test and Calibration
Information Stored	Bump/Cal Logs, Individual Monitor Event Logs, Firmware and Unit Configurations
Gases Available	CO, H2S and O2
Unit Compatibility	Works with SGT
Calibration Gas	Compatible with 58L cylinders
Charging Adaptor	12V, 3A



Accessories

IR Link

