

*auto range + Type K/J Thermometer
Humidity, Light, Anemometer*

SOUND LEVEL METER

Model : SL-4112P

ISO-9001, CE, IEC1010



EM-910P (for SL-4112P)

Features :

- * 30-130 dB, auto range, manual range
- * Frequency and time weighting meet IEC 61672 class 2.
- * A or C frequency weighting.
- * Fast/Slow time weighting, peak hold.
- * Data hold, Record (max., min.).
- * AC output, RS232/USB interface.
- * Data logger.
- * Optional data transmission software, SW-E2005, SW-DL2005.
- * Type K Temp. : -100 to 1300 °C, °C/°F
- * Type J Temp. : -100 to 1100 °C, °C/°F
- * Optional type K Temp. probes : TP-01, TP-02A, TP-03, TP-04, TP-05.
- * DC 1.5V battery (UM-4/AAA) x 6 or DC 9V adapter in.
- * Optional wind shield ball, SB-01.
- * Optional USB cable, USB-01.
- * Optional data acquisition softwares, SW-U801-WIN, SW-E802.
- * EM-910P probe : Humidity/Temp., Lig and Anemometer.
- * EM-910P probe is the standard probe SL-4112P.

Lutron

LUTRON ELECTRONIC

The Art of Measurement