

Victor 81D

VICTOR81D Technical data		
Basic Function	Range	Basic accuracy
DC Voltage	400mV/4V/40V/400V/600V	$\pm(0.5\%+4)$
AC Voltage	400mV/4V/40V/400V/600V	$\pm(0.8\%+6)$
DC Current	400uA/4000uA/40mA/400mA/10A	$\pm(1.0\%+10)$
AC Current	400uA/4000uA/40mA/400mA/10A	$\pm(1.5\%+10)$
Resistance	400 Ω /4k Ω /40k Ω /400k Ω /4M Ω /40M Ω	$\pm(0.8\%+4)$
Capacitance	4nF/40nF/400nF/4uF/40uF/100uF	$\pm(3.5\%+8)$
Frequency	1Hz/10Hz/100Hz/1kHz/10kHz/100kHz/30MHz	$\pm(0.5\%+10)$
Celsius	(-20-1000) $^{\circ}$ C	$\pm(1.0\%+5)$

Special Function

Diode test&Continuity buzzer	√
Low battery indication	√
Data hold	√
Auto power off	√
Function protection	√
10A fuse	√
Shockproof protection	√
self-resume fuse protection for mA	√
Unit symbol display	√
Relative value measurement	√
Duty cycle measurement	0.1%-99.9%
Input impedance	10M Ω
Sampling rate	4 times/s
AC Frequency response	(40-400)Hz
Operation way	Auto range
Max.Display	4 3/4 (3999)
LCD size	57×33mm
Battery	3V(1.5×2)

General Characters

Product color	Case: dark gray; Holster color (yellow)
Product Net Weight	Approx: 200g(including battery)
Product Dimension	145×80×30mm
Standard Accessories	Test leads/battery/instruction manual/TP01 K style temperature probe.
Standard inner packing	Color box
Standard Quantity Per Carton	60 pcs
Carton size	470×325×35mm
Standard Gross Weight	Approx:20kg