

Features

VC8045-II Bench-Type Digital Multimeter

.4 2/1 high performance Bench-Type Digital Multimeter, crystal display.

. It can be used to measure DC and AC voltage, DC and AC current, Resistance, Capacitance, Hz, hFE, Diodes and continuity

The max. voltage measuring can up to 1000V DC or AC peak value. Resolution can be 10uV, and

Current measuring can up to 20A, it also has the function of polarity auto-change, backlight displaying and directly reading.

. For AC measuring, it is performed by high accuracy true RMS, has the feature of width measuring and to get accurate RMS f or AC flow of any wave shape



VICTOR VC8045 II

| Basic Function | Range | Basic accuracy |
|----------------|-----------------------------------|----------------|
| DC Voltage | 200nV/2V/20V200V/1000V | ± (0.05%+3) |
| AC Voltage | 200nV/2V/20V200V/750V | ± (0.8%+80) |
| DC Voltage | 200uA/2000uA/20mA/200mA/2A/20A | ± (0.35%+10) |
| AC Voltage | 200mA/2A/20A | ± (0.8%+80) |
| Resistance | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ | ± (0.1%+5) |
| Frequency | 20Hz/200Hz/2KHz/20KHz/200KHz/2MHz | ± (1.0%+20) |
| Capacitance | 20nF/200nF/2uF/20uF/200uF/2000uF | ± (3.5%+20) |

| Special Function | |
|-----------------------|-----------------------|
| Diode test | ✓ |
| Triode test | ✓ |
| Continuity buzzer | ✓ |
| Overload protection | ✓ |
| Input impedance | 10 MΩ |
| AC Frequency response | 3 times/s |
| Sampling rate | 40-50kHz |
| Operation way | Manuak range |
| Max. Display | 19999 |
| Dimension | 245 x 220 x 82 mm |
| Weight | Approx:1Kg |
| Power | AC220V/110V 50Hz/60Hz |