

Victor VC890C+

Basic Function	Range	Basic accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm(0.5\%+3)$
AC Voltage	2V/20V/200V/750V	$\pm(0.8\%+5)$
DC Current	20uA/2mA/200mA/20A	
	200uA/20mA/200mA/20A	$\pm(0.8\%+10)$
AC Current	2mA/200mA/20A	
	20mA/200mA/20A	$\pm(1.0\%+15)$
Resistance	200Ω/2kΩ/20kΩ/200kΩ /2MΩ/20MΩ	
	200Ω/2kΩ/20kΩ/200kΩ/20MΩ	$\pm(0.8\%+3)$
Capacitance	20nF/2uF/200uF	$\pm(2.5\%+20)$
Celsius	$(-20\sim 1000)^{\circ}\text{C}$	$\pm(1.0\%+5)$

Special Function	
Diode	C
Transistor	√
Continuity buzzer	√
Low battery indication	√
Data Hold	√
Auto power off	√
Function protection	√
Restorable Fuse protection	√
Shock proof protection	√
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	40~400Hz
Operation way	Manual range
Max. Display	1999
LCD size	55×43mm
Battery	9V(6V22)

Product color	Case: dark gray; Holster color yellow
Product Net Weight	Approx:270g
Product Dimension	168×87×47mm
Standard Accessories	Test leads/battery/instruction manual/TP01 temperature probe
	with temperature function / Testing accessories
Standard inner packing	Color box
Standard Quantity Per Carton	30 pcs
Carton size	396×312×433mm
Standard Gross Weight	Approx:17.5kg