

APECH

AC/DC CLAMPMETER

MODEL AC-386



Basic function	Range	Accuracy
DCV	600mV/6V/60V/600V	±(0.5%+3)
	LoZ 0V~600V	±(2.0%+10)
ACV	6V/60V/600V	±(0.8%+5)
	LPF 0V ~ 600V	±(4.0%+8)
	LoZ 0V ~ 600V	±(2.0%+10)
DCA	60A/600A/800A	±(1.5%+5)
ACA	60A/600A/800A	±(1.5%+5)
Resistance	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/60MΩ	±(0.8%+1)
Capacitance	6nF/60nF/600nF/6uF/60uF/600uF/6MF/60MF	±(2.5%+5)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±(0.1%+3)
Temperature	(-40 to 1000)°C, (-40 to 1832) °F	±(1.0%+5)

Special Function:

Model	AC-386
Diode test	✓
Continuity test	Less than 50Ω
LoZ V function	✓
Low battery indicator	Approx. less than 2.6 V
Data hold	✓
NCV	✓ (2 detecting way)
Auto power off	About 15 minutes
True RMS test	✓
LPF function	✓
Function protection	✓
Clamp light function	✓
Backlight display	✓
Input impedance	10MΩ
Sampling rate	3 times/s
AC frequency response	40-2kHz
Operation method	Auto or manual range
Max display	6000
Clamp opens	28mm
Battery	3V (2*AAA battery)

ACCESSORIES INCLUDED :

