

APECH

CAPACITANCE METER

AM-568CAP

Feature :

New type holster, streamline design, Large LCD , Max display 3 ½ (1999 Digit) makes the reading clearly, Strong antimagnetic and anti-jamming performance; full protect function, capacitor with the function of self discharge; Unit symbol display, easy to operate

- Low battery indicator, fast sampling



Specification :

RANGE	RESOLUTION	ACCURACY	TEST FREQUENCY	MAX DISPLY
200pF	0.1pF	±(0.5%+1)	800Hz	199.9pF
2nF	1pF	±(0.5%+1)	800Hz	1.999nF
20nF	10pF	±(0.5%+1)	800Hz	19.99nF
200nF	100pF	±(0.5%+1)	800Hz	199.9nF
2uF	1000pF	±(0.5%+1)	800Hz	1.999uF
20uF	0.01uF	±(0.5%+1)	80Hz	19.99uF
200uF	0.1uF	±(0.5%+1)	8Hz	199.9uF
2000uF	1uF	±(2%+1)	8Hz	1999uF
20mF	10uF	±(2%+2)	8Hz	19.99mF
200mF	100uF	±(5%+10)	8Hz	199.9mF
OTHERS FUNCTION :				
Low battery indication		Approx. less than 7.5V		
capacitor discharge protect		√		
Auto power off		It will power down about 30 minutes if no any measure.		
Anti-shock protect		√		
Sampling rate		3times/s		
Operation way		Manual range		
Max. display		1999		
LCD size		65×41mm		
Battery		9V (6F22)		
Power dissipation		Quiescent current approx. 3mA		
Weight		290g (including battery)		
Meter size		185×93×35mm		
Standard accessory		Test leads, battery, manual		